

Purpose-built 2U for growing scale-out solutions

The Dell EMC PowerEdge R750xs, with 3rd generation Intel® Xeon® Scalable processors, is purposefully designed with distinctive, customer-defined requirements to deliver enterprise performance for scale-out environments.



Innovate at scale with challenging and emerging workloads

The new Dell EMC PowerEdge R750xs is a 2U, dual-socket, feature-optimized server with an ideal selection of CPU, I/O, and storage performance for scale-out environments. With it, you can:

- Add additional power and cores: Up to two 3rd generation Intel® Xeon® Scalable processors, up to 32 cores per socket
- Accelerate in-memory workloads: Up to 16 DDR4 RDIMMS, 3200 MT/sec
- Improve throughput, reduce latency: With up to 5 PCIe Gen4 slots, OCP 3.0 for network cards, and SNAP I/O support
- Include flexible storage: Up to 12x 3.5" SAS/SATA HDDs or SSDs; or up to 16x 2.5" SAS/SATA HDDs or SSDs, and 8 NVMe drives
- Enable virtualization, medium VM density or VDI, and software-defined storage node workloads

Increase efficiency and accelerate operations with autonomous collaboration

The Dell EMC OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell EMC OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

- Built-in telemetry streaming, thermal management, and RESTful API with Redfish offer streamlined visibility and control for better server management
- Intelligent automation lets you enable cooperation between human actions and system capabilities for added productivity
- Integrated change management capabilities for update planning and seamless, zero-touch configuration and implementation
- Full-stack management integration with Microsoft, VMware, ServiceNow, Ansible and many other tools for on-premise, edge and cloud environments

Built-in proactive resilience through a complete portfolio of solutions

From the silicon and supply chain all the way to asset retirement, know that your servers are safe and secure with innovative Dell EMC and Intel technologies. We give you the confidence of cyber resilience with enterprise class security that minimizes risk for any organization, from small business to hyperscale.

- Start strong with platform security features, even before the server is built, including Secured Component Verification and Silicon Root of Trust
- Stay strong with continuous innovations that bolster cyber resilience, like OpenManage Secure Enterprise Key Manager and Automatic Certificate Enrollment
- Outmaneuver threats with intelligence, automation, and recovery tools that include iDRAC9 Telemetry, BIOS live scanning, and Rapid OS recovery

PowerEdge R750xs

The Dell EMC PowerEdge R750xs offers compelling performance, high-speed memory and capacity, I/O bandwidth and storage to address data requirements – Ideal for:

- Virtualization
- Medium VM density or VDI
- Software-defined storage node

Feature	Technical Specifications	
Processor	Up to two 3rd Generation Intel Xeon Scalable processors with up to 32 cores	
Memory	<ul style="list-style-type: none"> 16 DDR4 DIMM slots, supports RDIMM 1 TB max, speeds up to 3200 MT/s Supports registered ECC DDR4 DIMMs only 	
Storage controllers	<ul style="list-style-type: none"> Internal controllers: PERC H345, PERC H745, PERC H755, PERC H755N, HBA355i, S150 Internal Boot: Internal Dual SD Module, Boot Optimized Storage Subsystem (BOSS1): HWRAID 2 x M.2 SSDs, USB External PERC (RAID): PERC H840, HBA355e 	
Drive Bays	<p>Front bays:</p> <ul style="list-style-type: none"> 0 drive bay Up to 8 x 3.5-inch SAS/SATA (HDD/SSD) max 128 TB Up to 12 x 3.5-inch SAS/SATA (HDD/SSD) max 192 TB Up to 8 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 61.44 TB Up to 16 x 2.5-inch SAS/SATA (HDD/SSD) max 122.88 TB Up to 16 x 2.5-inch (SAS/SATA) + 8 x 2.5-inch (NVMe) (HDD/SSD) max 184.32 TB <p>Rear bays:</p> <ul style="list-style-type: none"> Up to 2 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 15.36 TB 	
Power Supplies	<ul style="list-style-type: none"> 600 W DC/240 V 600 W Platinum AC/100 - 240 V 800 W DC/240 V 800 W Platinum AC/100 - 240 V 1100 W DC/-48-(-60) V 1100 W DC/240 V 1100 W Titanium AC/100 - 240 V 1400 W DC/240 V 1400 W Platinum AC/100 - 240 V 	
Cooling options	Air cooling	
Fans	<ul style="list-style-type: none"> Standard fans/High performance Silver fans/High performance Gold fans Up to six hot swap fans 	
Dimensions	<ul style="list-style-type: none"> Height – 86.8 mm (3.41 inches) Width – 482.0 mm (18.97 inches) Depth – 707.78 mm (27.85 inches) – without bezel 721.62 mm (28.4 inches) – with bezel 	
Form Factor	2U rack server	
Embedded Management	<ul style="list-style-type: none"> iDRAC9 iDRAC Service Module iDRAC Direct Quick Sync 2 wireless module 	
Bezel	Optional LCD bezel or security bezel	
OpenManage Software	<ul style="list-style-type: none"> OpenManage Enterprise OpenManage Power Manager plugin OpenManage SupportAssist plugin OpenManage Update Manager plugin 	
Mobility	OpenManage Mobile	
Integrations and Connections	<ul style="list-style-type: none"> BMC Truesight Microsoft System Center OpenManage Integrations Red Hat Ansible Modules VMware vCenter and vRealize Operations Manager 	<ul style="list-style-type: none"> IBM Tivoli Netcool/OMNibus IBM Tivoli Network Manager IP Edition Micro Focus Operations Manager OpenManage Connections Nagios Core Nagios XI
Security	<ul style="list-style-type: none"> Cryptographically signed firmware Secure Boot Secure Erase Silicon Root of Trust System Lockdown (requires iDRAC9 Enterprise or Datacenter) TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ 	
Embedded NIC	2 x 1 GbE LOM	
Network Options	1 x OCP 3.0	
GPU Options	Not supported	
Ports	<p>Front Ports</p> <ul style="list-style-type: none"> 1 x iDRAC Direct (Micro-AB USB) port 1 x USB 2.0 1 x VGA <p>Internal Ports</p> <ul style="list-style-type: none"> 1 x USB 3.0 (optional) 	<p>Rear Ports</p> <ul style="list-style-type: none"> 1 x USB 2.0 1 x Serial (optional) 1 x USB 3.0 2 x Ethernet 1 x VGA
PCIe	Up to 5 x PCIe Gen4 slots / 1 x PCIe Gen3 slots	

Feature	Technical Specifications
Operating System and Hypervisors	<ul style="list-style-type: none"> • Canonical Ubuntu Server LTS • Citrix Hypervisor • Microsoft Windows Server with Hyper-V • Red Hat Enterprise Linux • SUSE Linux Enterprise Server • VMware ESXi For specifications and interoperability details, see Dell.com/OSsupport .
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com/OEM .

Recommended support and services

Dell ProSupport Plus for critical systems or Dell ProSupport for premium hardware and software support for your PowerEdge solution. Consulting and deployment offerings are also available. Contact your Dell representative today for more information. Availability and terms of Dell Services vary by region. For more information, visit www.delltechnologies.com/Services.

Dell Technologies on demand

Consume technology, infrastructure and services any way you want with Dell Technologies on Demand, the industry's broadest end-to-end portfolio of flexible consumption and as-a-Service solutions. For more information, visit: www.delltechnologies.com/ondemand.

Discover more about PowerEdge servers



Learn more about our PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on Twitter



Contact a Dell Technologies Expert for [Sales](#) or [Support](#)